



# GXOW.R21161 - Flush and Surface Bolts, Automatic Type

## Flush and Surface Bolts, Automatic Type

See General Information for Flush and Surface Bolts, Automatic Type

### THASE ENTERPRISE CO LTD

R21161

33 CheXin Rd Sanzhi District

New Taipei, 25242 TAIWAN

Models 510M, 610M, FB510M, FB560M, FB610M, FB620M top and bottom flush bolt units for use on metal doors measuring up to 1219 mm (4 ft) wide and 2438 mm (8 ft) high, rated up to and including 3 hrs.

Models 510W, 610W, FB510W, FB560W, FB610W, FB620W top and bottom flush bolt units for use on wood or plastic covered composite type fire doors measuring up to 1219 mm (4 ft) wide and 2438 mm (8 ft) high, rated up to and including 1-1/2 hrs.

Models 610M/FL001, FB610M/FL001 top flush bolts only for use on metal doors measuring up to 1219 mm (4 ft) wide and 2438 mm (8 ft) high, rated up to and including 3 hrs.

Models 610W/FL001, FB610W/FL001 top flush bolts only for use on wood doors measuring up to 1219 mm (4 ft) wide and 2438 mm (8 ft) high, rated up to and including 20 min.

Model FB810 (top or bottom) automatic flush bolts for use with Classified hollow-metal steel stiffened doors rated up to and including 3 hr; wood and plastic-covered composite doors rated up to and including 1-1/2 hr; and wood core doors rated 20 min. The Model FB810 shall be provided in a pair and designated the Model FB820, combined with the Model FB710 self-latching type flush bolt and designated as the Model FB780, or combined with an auxiliary fire pin and designated as the Model FB810/FL001.

Last Updated on 2014-06-30

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"