

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-000548-01

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation), this certificate applies to the construction product(s)

Product(s): Building hardware - Locks and latches - Mechanically operated locks,

latches and locking plates (refer to attached appendix for details and

conditions)

Placed on the market Euro Door Products FZE.

under the name or trademark of: Hamriya Free Zone, Phase 2, E-LOB 109, F64, Sharjah, U.A.E.

and produced in the manufacturing plant(s):

SG-15309

Intended use: When used with an appropriate door closing device on fire and/or smoke control doors to fulfil the self-closing requirement of such doors, and

thereafter to ensure that the door remains shut.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the

standard(s):

EN 12209:2003/AC:2005

Under System 1 for the performance set out in this certificate are applied and that the performance of the construction product fulfils all the prescribed requirements for these performances.

This certificate **replaced 0359-CPR-000548-01** first issued on **2017-05-17** and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to asses the performances of the declared essential characteristics, do not change, and the construction product, and the manufacturing conditions in the plant are not modified significantly, unless suspended or

withdrawn by the product certification body.

The issued document and statement(s) herein makes reference only to a presumption of conformity in accordance with the CPR Regulations EU 305/2011 (as amended). However, it is the manufacturer's or their authorised representative's sole responsibility to affix the CE logo and, by doing so, confirms full compliance and conformity to all other European mandatory directives and regulations that may also apply.

0905

CE

Signature:

Name:

Date: 2020-08-26

Issue: 01

Dipl.-Ing. Roland Heine Position: Certification Manager

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Page 1 of Δ RFT_FII_NIR_OP_23_V2_a



CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-000548-01

APPENDIX TO: Certificate of Constancy of Performance

Brand: EDP

Model Ref: EL 5572Z, EL 6072Z, EL 6572Z, EL 7072Z, EL 8072Z, EL 4585Z, EL 5085Z, EL 6085Z, EL 5572ZL, EL 6072ZL,

EL 6572ZL, EL 5572ZD, EL 6072ZD, EL 6572ZD, EL 5572ZN, EL 6072ZN, EL 6572ZN, EL 5578ZWC,

EL 6078ZWC, EL 6578ZWC

Table A1. Product description for mechanically operated locks, latches and locking plates from Euro Door Products FZE.

Function	Model Number	Backset (mm)	C to C distance (mm)
Sash lock	EL 5572Z	55	72
Handle only operate latch, cylinder operate latch and dead bolt.	EL 6072Z	60	72
	EL 6572Z	65	72
	EL 7072Z	70	72
	EL 8072Z	80	72
	EL 4585Z	45	85
	EL 5085Z	50	85
	EL 6085Z	60	85
Passage latch	EL 5572ZL	55	72
Only latch bolt function, handle operate latch.	EL 6072ZL	60	72
	EL 6572ZL	65	72
Deadlocking bolt	EL 5572ZD	55	72
Only deadbolt function, cylinder operate deadbolt.	EL 6072ZD	60	72
	EL 6572ZD	65	72
Night latch	EL 5572ZN	55	72
Handle operate latch, cylinder operate latch.	EL 6072ZN	60	72
	EL 6572ZN	65	72
Bathroom lock	EL 5578ZWC	55	78
Latch is operated by handle, deadbolt is operated by turn.	EL 6078ZWC	60	78
	EL 6578ZWC	65	78

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Deutschland GmbH, Stangenstraße 1, 70771 Leinfelden-Echterdingen
Tel.: +49 711 27311-0 E-Mail: nb0905@intertek.com Web: www.intertek.de

9661 Page 2 of 4 RET_FILENR_∩P_23√2a



CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-000548-01

APPENDIX TO: Certificate of Constancy of Performance

Table A2. Mechanical test reports & product classification for mechanically operated locks, latches and locking plates ^{a, b} from Euro Door Products FZE.

Test Report	Model Number	Product Classification										
160920013GZU-001 160920013GZU-002	EL 5572Z, EL 6072Z, EL 6572Z, EL 7072Z, EL 8072Z, EL 4585Z, EL 5085Z, 6085Z	3	x	9	1 ^b	0	G	3	В	С	2	0
	EL 5572ZL, EL 6072ZL, EL 6572ZL	3	х	9	1 ^b	0	G	-	В	0	2	0
	EL 5572ZD, EL 6072ZD, EL 6572ZD	3	х	9	1 ^b	0	G	3	В	С	0	0
	EL 5572ZN, EL 6072ZN, EL 6572ZN	3	х	9	1 ^b	0	G	2	В	В	2	0
	EL 5578ZWC, EL 6078ZWC, EL 6578ZWC	3	Х	9	1 ^b	0	G	-	В	0	2	0

Table A3. Fire test report(s) for mechanically operated locks, latches and locking plates from Euro Door Products FZE.

Test Report	Model tested	Test Method	Fire Resistar	Fire Resistance (minutes)			
			Integrity (E)	Insulation (I)			
171101005SHF-BP-1	EL 8072Z	EN 1634-1:2014	260	17			
Test configuration: Sin Orientation: Open awa	gle leaf single action swing ay the furnace.	steel fire door assembly	У				
171101004SHF-BP-2	EL 8072Z	EN 1634-1:2014	111	111			
Orientation: Open into	gle leaf single action swing the furnace. le A1 were assessed as hav		bly				

Notes.

- a. The lock and plate shall be installed in accordance with the installation instructions for the product(s).
- b. Digit 4 grade "1" was based on the test result from fire resistance test (refer to Table A3).

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Tel.: +49 711 27311-0 E-Mail: nb0905@intertek.com Web: www.intertek.de

IANT POSE 4 OF A RELEBILINE.OD. 74

Intertek Deutschland GmbH, Stangenstraße 1, 70771 Leinfelden-Echterdingen



CERTIFICATE OF CONSTANCY OF PERFORMANCE

0905-CPR-000548-01

APPENDIX TO: Certificate of Constancy of Performance

Table A4. Annex ZA Related Information for Mechanically operated locks, latches and locking plates from Euro Door Products FZE.

Product:	Mechanical locks and their strike plates						
Intended use:	On fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors)						
Requirement/	Standard clause	Result Summary					
characteristic		For Latch lock:	For deadlocking				
		EL 5572Z, EL 6072Z, EL 6572Z, EL 7072Z, EL 8072Z, EL 4585Z, EL 5085Z, EL 6085Z, EL 5572ZL, EL 6072ZL, EL 6572ZL, EL 5572ZN, EL 6072ZN, EL 6572ZN, EL 5578ZWC, EL 6078ZWC, EL 6578ZWC	bolt: EL 5572ZD, EL 6072ZD, EL 6572ZD,				
Self-closing ability	Closing force (5.4.2)	Grade 9, Less than 15N	NPD (No Performance Determined)				
	Return force of latch bolt (5.1.2)	Pass, More than 2.5 N	NPD				
Durability of self- closing action	Durability of latch action (5.3.1)	Grade X 200 000 cycles	NPD				
Ability to maintain door in closed	Resistance to side load on latch bolt (5.2.1)	Grade 3 3kN	NPD				
position and not contribute to the spread of fire	Suitability for use on fire/smoke doors (5.5)	Pass Grade 1 (refer to Table A3)					
Control dangerous substances	Dangerous substances (5.1.1)	No dangerous substances declared for this product/intended use					

END OF DOCUMENT

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement, Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.

Intertek Deutschland GmbH, Stangenstraße 1, 70771 Leinfelden-Echterdingen

Tel.: +49 711 27311-0 E-Mail: nb0905@intertek.com Web: www.intertek.de