



GXSR.R21816 - Flush and Surface Bolts, Manual Type

Flush and Surface Bolts, Manual Type

See General Information for Flush and Surface Bolts, Manual Type

THASE ENTERPRISE CO LTD

R21816

33 CheXin Rd Sanzhi District

New Taipei, 25242 TAIWAN

Manual flush bolts, Model FB100, with 5/8 in. throw for use on swinging metal fire doors measuring up to 4 ft. wide and 8 ft. high with 1-3/4 in. thickness and rated up to and including 3 hr.

Manual flush bolts, Model FB100W, with 5/8 in. throw for use on swinging type, wood composite fire doors measuring up to 4 ft. wide and 8 ft. high with 1-3/4 in. thickness and rated up to and including 1-1/2 hr.

Last Updated on 2013-12-03

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"