

Model 16 series #6080 Panic Exit Device

#6080F Fire Rated Exit Device

(without dogging equipped)



Specification:

Conforms to ANSI/BHMB A156.3-2001 Grade 1 Requirement Standard UL Listed

For Doors : 1 3/4" thick standard to 2" doors (please specify when other than 1 3/4" thick)

Doors Width from 30"-48" (please specify when ordering)

Mounting : Furnished standard with Wood and Machine Screws, Thru Bolts are packed with Fire Rated Device.

Please refer to page 21 installation for reference.

Cover : Zinc

Chassis : Steel

Rail Assembly : Steel or Stainless Steel

End Cap : Steel or Stainless Steel

Hand : Non Handed, Trim Reversible

Latch Bolt : 5/8" throw, Stainless Steel for Fire Rated , Zinc for Panic Grade with SS Dead Latch.

Cylinder : Brass , Rim-Type 5-pin or 6-pin, 2 Keys, if required.

Strike : Zinc for Panic Grade ,Brass for Fire Rated Device;

both with Shim Plate adjustable with slotted holes for adjustments

Dogging Feature : Allen Key (not equipped on Fire Rated Device)

UL listed : Panic Hardware and Fire Rated 3 Hour Test Standard and conform to ANSI/BHMAA156.3-2001 Grade 1 Requirement Standard

Finish : Painted Silver/Aluminum and Durodic Finish

32D (Stainless Steel finish)

10B (Oil Rubbed Bronze finish)

Dimension:

Touch Bar Height to Finished Floor : 41"(1041mm) at Center

Touch Bar Projection : Neutral 2-5/8"(65mm)

Depressed 1-7/8"(47mm)

Center case (Head Cover) : L x W x H : 154mm x 55mm x 65mm

Device Length : 32-7/8"(834mm) for 36" door size

42-7/8"(1089mm) for 48" door size