



DT-F1500V - VERTICAL PANIC BAR



- For Doors: 36" width doors
1-3/4" to 2" thick doors.
Specify when order than 1-3/4" thick, up to 2" thick doors
- Mounting: Furnished standard with wood and machine screws.
Through bolts for fire rated device.
- Head Cover: Zinc or Stainless Steel
- Push Bar: Steel or Stainless Steel
- Rail: Steel or Stainless Steel
- End Cap: Steel or Stainless Steel
- Hand: Non-handed with reversible trim.
- Latch Bolt: Stainless Steel 3/4" throw with dead latch
- Cylinder: Brass, rim-type 5 pin, 2 key if required
- Strike: Stainless Steel with shim plate adjustable with slotted holes for
Easy adjustments
- Dogging: Alley key for standard non- fire rate device,
Not equipped on fire rated device.

Options

- Rail: 48" width door (specify when ordering)
- UL Listed: 3 hour fire rated devices
- DDS: Overlapping strike for double/ pair doors.
- Outside Trim: Please refer to "Outside Trims" page for more information.
- Alarm: Power by battery, On/ Off by key control

Dimensions

- Touch bar height to finish floor: 40" or 1016mm at centre
- Touch bar projection: Neutral 3-1/8" or 80mm
Depressed 2-9/16" or 65mm
- Device length: 32" for 36" door size
42" for 48" door size
- Top and bottom latch case: Top Case: Stainless Steel Pullman Latch
Bottom Case: Sliding Bolt
- Top and bottom rod length: 36"x 84" doors: top rod 915mm bottom rod 800mm
48" x 96" doors: top rod 1220mm bottom rod 800mm
- Finish: Painted: Aluminium or
Duronodic (please specify when ordering)
Solid Stainless Steel: Satin or
Polished

