



GVEV.R25111 Swinging Fire Door Closers

[Page Bottom](#)

Swinging Fire Door Closers

[See General Information for Swinging Fire Door Closers](#)**SUZHOU FUERDA INDUSTRY CO LTD**

R25111

WENZHOU INDUSTRY PARK

SHUANGFENG

TAICANG

SUZHOU, JIANGSU 215416 CHINA

Cam action concealed mounted type Model(s) C6000+**For self closing doors, without hold-open feature, concealed mounted type** Model(s) F6203G+**For self closing doors, without hold-open feature, concealed mounted type, size 3** Model(s) 1003-REC+**For self closing doors, without hold-open feature, overhead concealed mounted type, size 2** Model(s) C1020+**For self closing doors, without hold-open feature, overhead concealed mounted type, size 2-3** Model(s) C2013+**For self closing doors, without hold-open feature, overhead concealed mounted type, size 2-4** Model(s) C2014+**For self closing doors, without hold-open feature, overhead concealed mounted type, size 2-5** Model(s) C2035+**For self closing doors, without hold-open feature, overhead concealed mounted type, size 3** Model(s) C1030+**For self closing doors, without hold-open feature, overhead concealed mounted type, size 4** Model(s) C1040+**For self closing doors, without hold-open feature, overhead concealed mounted type, size 5** Model(s) C1050+**For self closing doors, without hold-open feature, surface mounted type** Model(s) 504BC+, F1602BC+, F1703BC+, F1704BC+, F1705BC+, F1725BC+, F1726BC+, F1736BC+, MH-2431xCOV+**For self closing doors, without hold-open feature, surface mounted type, size 2** Model(s) 430P+, B2W+ ; size 3, B3W+ ; size 4, B4W+ ; size 5, B5W+ ; size 6, B6W+ , C52BC+, CL8202+, CL8203+, DYN-2000+, F8202+, F8500+, F8902+, MH-1077+, SARO DC2/3+**For self closing doors, without hold-open feature, surface mounted type, size 2-3** Model(s) F8200+**For self closing doors, without hold-open feature, surface mounted type, size 2-4** Model(s) 300PBFCOV+, 300PCOV+, 5009+, 514+, 7400+, 7500+, CL-3870ADA+, DC50-AL+, DC50-DU+, DC8900AL+, DC8900DU+, DYN-1614+, F1714+, F8900+, F8900BC+**For self closing doors, without hold-open feature, surface mounted type, size 2-5** Model(s) 6115+, 9000+, CL-3870+, F8915BC+**For self closing doors, without hold-open feature, surface mounted type, size 2-6** Model(s) 3000+, 3200+, 4001+, 4001CNS+, 4041+, 4116+, 416+, 8116+, 9000-PBC+, 9000-PBF+, 9000-PBF/DA+, 9000-PDA+, 9016+, 9116+, CL-4840+, CL8400BF+, CL8600BF+, CL8600BFDA+, CL8844BF+, CR441+, CR441DA+, CR801+, CR801S+, DC41-AL+, DC41-DU+, DC8300AL+, DC8300DU+, DC8400AL+, DC8400DU+, DC9000PBC/BF AL+, DC9000PBC/BF DUR+, DYN-4401+, DYN-8500+, DYN-9000+, F1916+, F8100+, F8300+, F8400+, F8416BC+, F8416DA+, F8916BC+, MH-2461 DELXCOV+, MH-2461XCOV+, MH-5041xCOV+, N900PBF+, N900PBFD+, RGN900PBF+, SARO-BD 1-6+**For self closing doors, without hold-open feature, surface mounted type, size 3** Model(s) 7200+, 7300+, 730P+, C53BC+, CL-3353+, DYN-3000+, F1600+, F8903+, J4609**+, J4611**+**For self closing doors, without hold-open feature, surface mounted type, size 3-6** Model(s) 1036+, DYN-1636+, F8936BC+**For self closing doors, without hold-open feature, surface mounted type, size 4** Model(s) 4441+, C54BC+, CL-3084+, CL-3354+, DYN-4000+, F8904BC+**For self closing doors, without hold-open feature, surface mounted type, size 5** Model(s) 4551+, C55BC+, F8905BC+

+ - Also evaluated in accordance with Standard UL 10C, designed to be used with swinging type fire doors rated up to and including 3h.

Trademark and/or Tradename: "CRP" , "FRD" , "RAMCO"

[Last Updated on 2017-07-24](#)[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".